

## Vehicle Data

### Model : TGX 35.580 8X4-4 BL

Order: 6032/17050      Vehicle: 92X-0783  
**Customer:**            VV-AUTO GROUP OY 01530 VANTAA  
**Sales centre/country:** Finland  
**Place of production:** MÜNCHEN  
**Vehicle model:**        TGX 35.580 8X4-4 BL  
**Basic vehicle**         L 92X SL 64  
**Delivery date:**        27.10.2017

### Technical extent of delivery

Code	Customer Special Request	Designation
001AA		steering arrangement, left
005U3		Wheelbase 4200+1350+1450 mm
006LO		rear frame overhang 2000 mm
018OT		Engine D3876LF07 - 580 hp / 427 kW Euro 6 SCR 2900 Nm C-R OBD-C
02AAE		instrument panel km/h 'High-Line'
021GP		Gearbox software MAN TipMatic Profi (road deployment)
022QV		Gearbox MAN TipMatic 12 30 OD
023Q1		Fuel tank aluminium 590l, right and 80l AdBlue
025MH		front axle VOK-09 dropped
026EF		front springs parabolic 9,5 t
027AN		radiator and intercooler for up to 35 degrees ambient temperature
028AM		air suspension rear
029GA		Propshafts for standard load profile
03KAA		fuel tank fitted
030EE		steering wheel with height and inclination adjustment
032AB		MAN BrakeMatic (electronic brake system)
034NM		hypoid rear axle HYD-1370/HY-1350
035ET		Hypoid axle ratio i = 3.70
037AC		with differential lock in rear axle
038DS		aluminium disc wheels 10-hole 11.75-22.5 ALCOA Matt on trailing axle TL
038GS		Aluminium disc wheels 10-hole 11.75-22.5 ALCOA matt on 1st FA TL
038PY		aluminium disc wheels 10-hole 9.00- 22.5 ALCOA Matt on 1st RA TL
038RY		aluminium disc wheels 10-hole 9.00- 22.5 ALCOA Matt on 2nd RA TL
038XT		without spare wheel
041AH		trailing axle NOL-09 steered, lifting
042DM		Digital tachograph made by MAN
045CA		MAN EasyStart for TipMatic
05NAE		front panel unlockable from inside
050NH		XXL cab with high roof, 2440mm wide,2280mm long
051AP		comfort control module with top bunk
052AE		Storage box accessible from outside - flap unlocked from inside
058BH		Seat covers in Alcantara/leather
058NK		high-comfort driver's seat with air suspension, climate control and heating
059NR		Air-sprung comfort co-drivers seat with lumbar support, shoulder adjustment and heating
068AS		door extension
080AG		interior panelling in leather
116AE		visco fan
118AC		air deflector to stop dust swirling
118EK		Short mounting base (engine only)
118MA		EDC engine regulation

119EH		General PTO parameterisation
120KX		Flywheel side PTO with steering-pumpflange f=1.42 (85 Nm continuous load)
121FS		Gearbox functionality: Rock-free mode
121FT		Gearbox functionality: EfficientRoll
122I3		PTO NTX/10c without flange f=1.15 below
124AL		fuel filter
124AT		Heated additional fuel filter / water trap
124EA		fuel filter heating
128EC		Pressure sensor for air spring bellows
142AD		Preparation of remote download data interface for digital tachograph
142AF		calibrate tachograph
150MC		Window cleaning set
150WQ		Trunk-wood insert on instrument panel
153EW		water aux. heater with coolant pre- heater, EBERSPAECHER D5W
153EY		air auxiliary heater EBERSPÄCHER D4S
153KC		air conditioning system AC R134A with automatic temperature control without CFHC
159CX		cab insulation NORDIC (against cold)for XL, XLX and XXL cab
194AH		operator's manual in FINNISH
197SP		Mirror cover painted in platinum silver
201AS		air intake raised with dry air filter
201FA		fine dust and pollen filter
203EK		connection for external engine speedcontrol (ZDR)
203EU		Control module for external data exchange (customer-specific control module) with fleet management system in
205AB		Two-cylinder air compressor 720 ccm
206KB		Exhaust on right with bottom outlet
208AK		exhaust valve brake
210AA		flame starting system
211FT		single-disc clutch MFZ 430 reinforced
227AC		rear axle breather upswept
230AH		rear underride guard, round
230ER		front underride guard
230FC		lateral guard
232HA		synthetic bumper with integrated airdam
233FC		spoiler loose
236AF		cross member for trailer coupling
241AC		without platform mounting brackets
245XX		without spare wheel holder
256AF		steering wheel lock with immobiliser
257LY		multifunction leather steering wheel for 'L,LX,XL,XLX,XXL' cab
258HA		anti-lock braking system (ABS)
258NA		ECAS air suspension
259CA		disc brake for front axle
259CB		disc brake for rear axle
260FC		Duo-Matic quick coupling
262AC		brake connection 2-line
262AR		2-line brake connection at lh tail light
272FA		Entry lighting for driver and co-driver
276AC		Armrests for driver's seat
278EA		Air connection in cab
278EF		Air lines and air gun
280EU		stoneguard grille in front of radiator
283FG		Air sprung cab mounts for 'L,LX,XL,XLX,XXL'
284VW		Inspected by SPEC department BL 92X0783 0001
303AX		Lockable tank fastener - 1 u. ventilated for master key system
303CC		AdBlue lockable filler cap 1 pc.
309AA		Beam throw regulator

310EE		Halogen twin headlights H7 for right-hand traffic
310HQ		LED daytime driving lights (ECE R87-compliant)
310LH		Red/white interior lighting in cab roof
310NP		Automatic low-beam headlights with light sensor
318AA		marker lamps
318AK		lateral marker lights
319AR		reading lamp for driver
320AC		switches and wiring for cargo space lighting
321EC		central locking
321EH		Remote control for central locking
322CB		Tail lights with LED technology
324AC		Two-tone horn,electric
324CA		Two compressed air horns on the cab roof/roof spoiler
325AA		MAN Tronic (on-board computer)
325EP		Language 1 'Finnish' for display in instrument panel
325FA		Language 2 'German' for display in instrument panel
326CK		trailer socket for anti-skid system on frame end
326CW		7+7-pin 24 V trailer socket at end of frame
326FZ		Socket in cab 12V 2-pole and 24V 2-pole
327AF		battery main switch, mechanical
329CW		Two 12-V 225-Ah batteries
329ES		Battery box up to 230 Ah
329HC		Maintenance sign for batteries - 'maintenance-free'
331CY		28V three-phase alternator 120A 3360W Longlife Eco
339FM		Display in instrument panel for trailer data (axle load)
339FP		Display on the dashboard for operating data
343CK		Acoustic warning system for engaged reverse gear, can be deactivated
345AU		Maximum electronic speed limitation 89 km/h
345EA		cruise control
345EL		MAN EfficientCruise 2
345EP		ECO mode basic setting for MAN EfficientCruise
346CA		charging pressure indicator
350AB		MAN sound system
350IL		MAN TeleMatics 2 GPRS 'MAN TeleMatics service pack must be completed separately'
350LX		Antenna for Connectivity Board module and CB radio
350NP		MAN Media Truck Advanced radio, 12 Vwith seven-inch colour display and preparation for navigation
350OR		SD card, navigation system, WHOLE OFEUROPE
350TQ		Hands-free functionality 'Comfort' for two mobile phones (multi-function steering wheel and Bluetooth -capab
351AF		preparation for radiotelephone
351LE		Lane Guard System IV (LGS IV)
351MA		MAN VideoView - video input (one camera)
351US		AUX-IN/USB in the instrument panel
352ED		Preparation for additional cab lighting on cab roof
353CA		shunting light on step unit
357CA		Battery state monitoring
362AH		Stabiliser on both rear axles
363AA		Stabiliser for front axle
365AT		Moving-off aid does not conform to EU standard 97/27/EC
370CR		air dryer, heated
373AE		antifreeze effective down to -35 degrees
376FC		2 bunks with storage space (with aluminium frame)
376HC		Mattress for lower bunk with hardness zone divisions
376HN		Mattress for upper bunk
376KA		Bunk cover for bottom bunk
376KF		"Löwe" bed cover for for top bunk
380AH		windscreen of laminated glass tinted and heated
380CA		door windows tinted

381AA		cab rear wall without windows
381CE		All-round curtain
381CM		diagonal curtain
384CD		Safety belt display, driver's side
385AT		Side windows tinted behind B-post
386CC		Electric raising/sliding roof
387AF		Electric door window lifters for driver and co-driver
388AK		sun shade in front of windscreen
388AL		Sunblind for windscreen, electric
388CC		Roller sunblind on driver's door
389AC		handles left and right (on B-post)
389AD		handles left and right (on A-post)
390AG		Oddments tray in door armrest
390AO		Coolbox
390CV		2 pull-out drawers in centre of dashboard
390EF		2 waste paper bins between the seats
390SW		Bulkhead on transmission tunnel
392AR		kerb mirror, right, heated and electrically adjustable
392CL		EU front mirror on co-driver's side
392CW		Heated, electrically adjustable rear-view and wide-angle mirrors, rear-view mirror on co-driver's side with
392HA		Mirror brackets for body width 2500-2600 mm width 2500 mm
396AC		headlight washer system
396CE		Automatic wipers with rain sensor
398EK		desktop on coolbox or storage box
400AH		mudflap front
401CY		synthetic mudguards, 3-part, with mud flaps
404AP		spray reducer
405AC		Bonding set, separate
405AK		hazard-warning sign
405AR		hazard-warning lamp
407XX		Without jack
411AF		2 chocks
417AC		wheel bolt covers front
417AY		wheel stud covers LA/TA
434CH		Smoking package
538AF		carpeted engine tunnel
542DE		Confirmation of conformity to EC Directives
542FC		anti-noise package 80 dB (92/97EEC)
542NC		Registration as N3 vehicle, (GVW > 12t)
600AC		Fittings for right-hand traffic
797AA		to be entered in vehicle logbook: Zuggesamtgewicht 76.000 kg
798LF		Height over cab, unloaded up to 4000mm
798TM		A performance reduction of up to 25% is expected when a high GTW and extreme conditions are involved.
LQA03		cab acryl
LQA16		paint aerofoil acryl
LQA26		high roof in 2-pack acrylic
LQA46		mudguards behind cab in 2-pack acrylic
LQA48		Plastic bumper and front apron, 2K acrylic
LQA49		Door extension and step units, 2K acrylic
LQW01		chassis in water-based paint
LVS01		chassis TRAFFIC RED RAL 3020
LVS02		wheels ALU MATT -ALCOA-
LVS03		cab TRAFFIC YELLOW RAL 1023
LVS16		aerofoil TRAFFIC YELLOW RAL 1023
LVS26		paint high roof TRAFFIC YELLOW RAL 1023
LVS46		mudguards behind cab TRAFFIC YELLOW RAL 1023
LVS48		synthetic bumper and air dam TRAFFIC YELLOW RAL 1023

LVS49		door extension and steps TRAFFIC YELLOW RAL 1023
80001		2 Michelin 385/55R22,5 XFA2 ENGY TL
90001		4 Michelin 315/70R22,5 MW3DXDE TL 1
90002		4 Michelin 315/70R22,5 MW3DXDE TL 1
90003		2 Michelin 385/55R22,5 XFA2 ENGY TL

**Weights:**

Gross weight: 37000

1st front axle: 9000

2nd front axle: 0

3rd front axle: 0

Leading axle: 0

1st rear axle: 11500

2nd rear axle: 11500

Trailing axle: 9000

The prescribed data corresponds to current manufacturing regulations at the time of expression.  
Subject to change.

Version: 1.5.0.0